

534,589

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date  
21 May 2004 (21.05.2004)

PCT

(10) International Publication Number  
**WO 2004/041737 A1**

(51) International Patent Classification<sup>7</sup>: **C03B 37/018**

KANG, Byung-Chul [KR/KR]; 105-203 Yousung APT., Geomdan-dong, Buk-gu, 702-752 Daegu (KR).

(21) International Application Number:

PCT/KR2003/001069

(74) Agents: LEE, Sang-Yong et al.; 4F, Byukcheon Bldg., 1597-5, Seocho-dong, Seocho-gu, Seoul 137-876 (KR).

(22) International Filing Date: 30 May 2003 (30.05.2003)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language:

Korean

(26) Publication Language:

English

(30) Priority Data:

10-2002-0068943

7 November 2002 (07.11.2002) KR  
10-2003-0030247 13 May 2003 (13.05.2003) KR

(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


(71) Applicant (*for all designated States except US*): LG CABLE LTD. [KR/KR]; 19-20F ASEM Tower, 159, Samsung-dong, Gangnam-gu, Seoul 135-721 (KR).

## Published:

— with international search report

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: METHOD FOR MANUFACTURING AN OPTICAL FIBER PREFORM BY MCVD



(57) Abstract: Disclosed is a method for manufacturing an optical fiber preform in MCVD, which simultaneously performs an etching process for injecting a reaction gas for etching into a tube and a collapsing process for heating and collapsing the tube in order to minimize or eliminate an index dip existing at the center of the preform core. By using this method, the index dip phenomenon of the optical fiber preform can be minimized or eliminated, so it is possible to make an optical fiber having improved optical characteristics, particularly having improvement in a bandwidth and a polarization mode dispersion (PMD).

WO 2004/041737 A1